

Installation – TCS-4C_GSXR_K9.AA (revision_04, 07.02.2013)

Author – Mick Boasman

NEMESIS - TCS

Nemesis-TCS 'Traction Control System Installation manual Suzuki GSXR1000 K9 onwards with race and standard seat fairing

Kit part No.	TCS-4C_GSXR_K9.AA.xls
This application is designed for use with the Suzuki GSXR 1000 K9 fitted with standard and race seat fairing	

Speed pick up components	Part No	Checked	Qty
Suzuki GSXR front wheel speed sensor mounting bracket	CSD1374 - 03		1
Spacer D12, ID8.2, L5	CSD1392		2
M8 x 50 Cap head screw zinc	CSF1054		2
Speed sensor	23813030401		1
M6 Shoulder screw - 8mm dia shank	CSF1059		6
M6 x 16 Zinc Hex head cap screw - Speed sensor	CSP1019		1

Traction module components	Part No	Checked	Qty
Traction Control Module - 4c	CSP1048		1
Coil simulator module	CSP1050		1
TCS - 4C GSXR_K9 Mounting brk std seat	CSD1391		1
TCS - 4C Standard back panel	CSD1337		1
Bobbin - dia 10 x 17 M4 female	CSP1046		4
M4 x 8 button head allen screw s/s	CSF1045		8
M4 Spring washer s/s	CSF1050		8
M6 plain washer	CSF1061		4
M6 x 20 s/s cap head screw	CSP1038		4
M6 Nyloc s/s	CSF1063		4

Wiring	Part No	Checked	Qty
Main Wiring Suzuki GSX R K7/9	CSW1386		1
Front Wiring	CSW1371		1
Throttle signal - quick link (red)	CSP1015		1

Display module components	Part No	Checked	Qty
Display module	TC-Pod		1
Spacer - 11mm Dia x 6.5	CS1258		1
M6 x 35 s/s cap head screw - black	CSP1016		1
Push button assembly - blue/green TC-Pod	CS972		1
TC-Pod mount bkt - triple clamp	CSD1399		1
Spacer D12.8, ID8.2, L9.5	CSD1384		1
M8 x 40 Cap head screw zinc	CSF1065		1
M3 x 8 Hex button head	CSP1018		2

Miscellaneous components	Part No	Checked	Qty
Cable ties - 200mm x 4mm	CSP1021		10
Printed TCS system manual			1
Printed TCS-4C_GSXR_K9.AA manual			1
Nemesis-TCS stickers	CSP1022		6

Installation – TCS-4C_GSXR_K9.AA (revision_04, 07.02.2013)

Author – Mick Boasman

IMPORTANT – To be read by ALL installers and owners

Notes –

- This kit is designed for use on bikes fitted with a 'race type' seat fairing or standard seat unit. When fitted to a bike with standard seat unit it will be necessary to remove the plastic insert for holding the tool kit, this provides extra clearance for the TCS module.
- Power for the TCS system is via the Kill switch. After Kill-ON (bike in Run position) the TCS system needs 3 seconds to 'boot up', the engine will not start during this period.
- This kit uses the rear speed sensor on the gearbox. For customers who are not using our default sprocket ratio of 17/42 you will need the additional WinTC programming tool to change this.

Terms of use

The presence of the Nemesis-TCS does not take away the responsibility of the rider to operate the bike correctly within their own abilities, the track conditions and the laws of physics.

The system is designed to achieve greater on-track performance by the use of power modulation during wheel slip events, but in no way should it be considered possible for the system to recover from every conceivable loss of grip. The onus for safety always rests with the rider to stay within his or her own abilities, and to ensure that the 'on-bike' equipment is programmed, setup correctly, and an appropriate TC level selected for the skill of the rider, the bike and the track conditions.

This equipment is intended for racing or track day performance use only and where exhaust emission controls are not applicable.

By installing and using the Nemesis-TCS you automatically indemnify Competition Systems Ltd, our suppliers and our authorised dealers from all first party or third party loss or damages. Normal components warranty is not affected

Preparation. Remove these parts from the bike.

- All fairing panels
- Fuel tank
- Seat fairing
- Air box

TC-Display pod Fitting:

- Mount the display pod to the angled bracket using the M3x8mm screws.
- This bracket for mounting the display is supplied straight. For optimum installation on the Suzuki you should bend to a 40deg angle until the display is aligned correctly, as seen here.
- Fit the angle bracket to the upper triple clamp bolt using the 9.5mm spacer and longer bolt we provide.
- The wiring can be used to damp out some vibration and also a foam pad may be fitted between the bracket and the triple clamp, for the same purpose.
- Take care to ensure full steering movement without collision with the display pod
- Mount the CS972 switch assembly to the clutch lever assembly cylinder clamp using the M6x35 bolt and spacer provided. Connect the CS972 switch assembly to the TC-Pod via the 4-way connector of the TC-Pod wiring
- Do not secure any wires in place at this stage, as there will be further wires added in this region.
- If installing a pit limiter switch, mount it on the right brake lever assembly.




Installation – TCS-4C_GSXR_K9.AA (revision_04, 07.02.2013)

Author – Mick Boasman

Front Wheel Speed:

Your TCS kit comes with a dedicated bracket, sensor, spacers and different disc cap-head bolts.

- Remove the 6 bolts that secure the left brake disk in place and replace with the 6 new shoulder screws with higher profile heads. Fit to the manufacturer recommended torque and thread lock agent. **Under no circumstances should any alternative bolts be used.**
- Remove the two M8 spindle clamp bolts from the left fork and retain for future use. Use the two new longer M8x50mm bolts and bracket but do **not at this stage tighten these bolts.**
- Remove the rubber O ring from the sensor body and fit into the rebate of the sensor bracket.
- Apply a small amount of grease to the sensor body and push the sensor into the bracket. Lock in place using one of the M6x16 cap
- **Check the gap between the sensor face and the surface of one of the new disc bolts, it should be between 1mm and 3mm,** now tighten the two M8 bolts to the manufacturers recommended torque.
- The sensor maximum range is approx 4mm for smaller targets and 6mm for larger targets, therefore no other ferrous objects should be installed anywhere near this sensor
- **These are safety critical components and could result in wheel locking, brake failure or TCS damage if fasteners come loose.**



Do not forget the spacer

IMPORTANT – Care should be taken when using paddock stands not to damage the wiring or sensor mounting

Note that it may be necessary to modify the mudguard to clear the sensor body.

Wiring


The wiring provided in this kit comes in 2 parts to simplify the installation and enable crash damaged parts to be replaced without a major strip down.

Wiring – Front section

The front section wiring (part No.CSW1371) has connections for all of these elements

- 2C - Front speed sensor
- 2F - TC-Pod display
- 2G - Pit lane speed limiter switch
- 2E - PC communication point (4 way AMP)
- 2A - Chassis link
- 2B - Throttle signal (single wire)

This wiring to connector 2A is to be routed along the right side of the bike




Installation – TCS-4C_GSXR_K9.AA (revision_04, 07.02.2013)

Author – Mick Boasman

Wiring / Front - Throttle

The throttle input is the single wire 2B of this loom . This needs to be attached to the signal wire (pin A) of the standard bike throttle plate position connector using the red quick link provided in the kit, as shown in the steps below and the image to the right.

Note that the signal wire is supplied long and may be shortened as necessary



<p>The quick link is made up of three parts as seen here on the right:</p>	
<p>Using the green section with the slot, push it over the orange throttle signal wire of the bike loom until the wire rests at the bottom of the slot:</p>	
<p>The large red centre section must be fitted the correct way around or the link will not work. Locate the end with the sharp pointed tip protruding from the end of the outer body and screw this end onto the green section until it rests firmly against the wire. The sharp tip will pierce the outer sleeve but not sever the inner core of the wire:</p>	
<p>Strip back the sleeve of the throttle input wire on the TCS loom so that 8mm of inner metal core is exposed. Push this into the red cap as seen here on the right with inner core showing:</p>	
<p>Screw this cap and wire into the main body ensuring that metal inner core and wire cores are sandwiched and held securely.</p> <p>Shrink sleeving can be put over this quick link if required.</p>	

Wiring / Front – TC-Pod display

Connect the front wiring loom to the TC-Pod display via the 8 way connector 2F

Wiring / Front – front wheel speed

Route the front speed wiring 2C across the front of the bike and following the same route as the brake line to the left calliper, connect it to the front speed sensor. The wiring for sensor must be routed taking all of the following into consideration.

- Movement of forks
- Rotation of the steering
- Positioning of paddock stands

Wiring / Front – PC connector


The 4 way PC connector should remain accessible but securely cable tied to the existing harness.

Wiring / Front – Pit limiter switch

The 2 way pit limiter switch connector can be cable tied out of the way if not needed or plugged into the dedicated red switch assembly CSP1041

Installation – TCS-4C_GSXR_K9.AA (revision_04, 07.02.2013)

Author – Mick Boasman



Wiring – Rear section / Ignition coils

Route this loom section initially along the left side of the bike following the standard wiring route, once in front of the battery, this loom section must re-route to the right side of the bike and on towards the coils.

The following 4 connections are all ignition coil INPUT signals from the bike to the TCS unit

- A - Connect to Coil 1 wiring from bike wiring loom
- B - Connect to Coil 2 wiring from bike wiring loom
- C - Connect to Coil 3 wiring from bike wiring loom
- D - Connect to Coil 4 wiring from bike wiring loom

The following 4 connections are all ignition coil OUTPUT signals from the TCS to the drive the ignition coils


- E - Connect to Coil 1 on the bike
- F - Connect to Coil 2 on the bike
- G - Connect to Coil 3 on the bike
- H - Connect to Coil 4 on the bike

IMPORTANT – It is vitally important that the coil inputs and outputs are connected correctly or the bike may not start on all cylinders, or may even damage the engine.

Wiring – Rear speed

Locate the connector of the rear speed sensor and use connections **K** and **L** to bridge this junction. In this way the rear speed signal is shared between the TCS module and the dashboard/ECU.

The speed sensor connector is a 3 way black connector located above the gearbox to the left side of the bike. If you are unsure, trace the wire to the sensor which is located on the front sprocket cover.



Wiring – Battery ground

This vital connection **M** must be connected directly to the battery negative connector, not to the engine block or any other ground source.

IMPORTANT – Failure to fit the ground securely can lead to misfire / engine not starting / TCS module damage. This is the main power ground for the coil system.

Wiring – Front link

Connector **P** should be routed along the right side of the bike all the way to connect up with 2A from the front loom.

Wiring – Quick shifter input

Connector **Q** is available for use with most type of OFF/ON switch type quick shifter.

Installation – TCS-4C_GSXR_K9.AA (revision_04, 07.02.2013)

Author – Mick Boasman

Pin 1 – Vbat power



Pin 2 – Ground

Pin 3 - Signal

For more information on quick shifter connections please refer to the 'System manual'

Wiring – TCS module and ground

Connect the main wiring loom to the TCS module. It is vitally important that the small ground wire with the 4mm eye (**N**) be connected securely to the M4 stud as seen here using the M4 Nyloc nut. Without this the module or coils could be damaged as well as TCS not functioning correctly.



This bracket is then held to the sub frame under the seat lock cross-member. We provide longer screws, washers and M6 Nyloc nuts for this purpose.


Assemble the rubber mounts to the TCS module first and then fit the module to the mounting bracket. The end result should have the TCS connector central with the aperture of the bracket and pointing upwards. The module should also be horizontal

IMPORTANT – Failure to fit the module in the orientation shown and mounted on a horizontal axis will significantly affect the functionality of the TCS system.

Wiring – Coil correction device

The module highlighted in this picture must be plugged in at all times. Without this the bike will stop within 2 seconds and identify an ignition coil error.

The module requires no special mounting or orientation and may be secured in any convenient place



PC Setup

Your TCS module should be loaded with the following bike :

BIKE - Suzuki_K9_K11_C.BIKE

TYRE – To suit your installation

CONFIG - TCS_4C_Base_35_02.CONFIG

Default rear sprockets for maps are: 17/42

Gear box teeth - 4

Status **Position** offset value –

Stronger - **0.21 to 0.32** – Refer to **WinTC View Data**

Normal - **0.32 to 0.37** – Refer to **WinTC View Data**

Weaker - **0.37 to 0.47** – Refer to **WinTC View Data**

Note : The WinTC installation guide can be found in the manual - Win-TC 4C manual_v2.05_a.pdf